

# CE TEST REPORT

for

Wireless mite removal device

Model: LP-018


Prepared for: Wenzhou Laipin Electronic Technology Co., Ltd.  
West side of 104 National Highway at Lan Ganqiao intersection, Wanquan  
Town, Pingyang County, Wenzhou City

Prepared by: RED Laboratories Inc.  
Room 101, Building A, Zhengtailai Hi-Tech Innovation Park, Yintian  
Creative Park, Yantian Community, Xixiang Subdistrict, Bao'an District,  
Shenzhen, Guangdong, China

TEL: +86-0755-23080724

Report Number: RL241022078235ED-AM  
Date of Test: Oct. 17, 2024 ~ Oct. 22, 2024  
Date of Issue: Oct. 22, 2024

Tested By:



Reported By:



Reviewed By:



*The results detailed in this test report relate only to the specific sample(s) tested. It is the Application's responsibility to ensure that all production units are manufactured with equivalent EMC characteristics. This report is not to be reproduced except in full, without written approval from RED Laboratories Inc.*

## Table of contents

<b>1.0 General Information</b> .....	3
1.1 Client Information.....	3
1.2 General Description of E.U.T.....	3
1.3 Test Facility:.....	3
<b>2.0 List of Measurement Equipment</b> .....	4
<b>3.0 Technical Details</b> .....	6
3.1 Investigations Requested.....	6
3.2 Test Standards.....	6
3.3 Performance Criteria.....	6
3.4 Test standards and Results Summary Tables.....	7
3.5 Measurement Uncertainty (95% confidence levels, k=2).....	7
<b>4.0 Electromagnetic Interference Test results</b> .....	8
4.1 Power Line Conducted Emission Test.....	8
4.2 Disturbance Power Test.....	11
4.3 Radiated Emission Test.....	14
4.4 Harmonic Current Emissions.....	17
4.5 Flicker and Voltage Fluctuation.....	18
<b>5.0 Immunity Test</b> .....	19
5.1 Electrostatic Discharge.....	19
5.2 RF field strength susceptibility (80MHz----- 1000MHz).....	20
5.3 Electrical Fast Transient/Burst (EFT/B) immunity test.....	21
5.4 Surge test.....	22
5.5 Conducted immunity test.....	23
5.6 Voltage Dips/Interruptions immunity test.....	24
<b>6.0 CE Label</b> .....	25
<b>7.0 Photos of testing</b> .....	26
<b>8.0 Photographs – E.U.T.</b> .....	27

**1.0 General Information****1.1 Client Information**

Application:	Wenzhou Laipin Electronic Technology Co., Ltd.
Address of Application:	West side of 104 National Highway at Lan Ganqiao intersection, Wanquan Town, Pingyang County, Wenzhou City
Manufacturer:	Wenzhou Laipin Electronic Technology Co., Ltd.
Address of Manufacturer:	West side of 104 National Highway at Lan Ganqiao intersection, Wanquan Town, Pingyang County, Wenzhou City

**1.2 General Description of E.U.T.**

Product Name:	Wireless mite removal device
Model:	LP-018
Additional Model:	N/A
Trade Mark:	N/A
Power Supply:	Input: 5V, 2A Rated power: 120W
Memo:	According to the user's manual
Model Difference:	N/A
Remark:	N/A

**1.3 Test Facility:**

Name of Test Lab:	RED Laboratories Inc.
Address of Test Lab:	Room 101, Building A, Zhengtailai Hi-Tech Innovation Park, Yintian Creative Park, Yantian Community, Xixiang Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Telephone:	+86-0755-23080724

2.0 List of Measurement Equipment					
Conducted emission					
Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
EMI Test Receiver	ESPI	101604	RS	2024/6/17	2025/6/16
LISN	ENV 216	102796	RS	2024/6/17	2025/6/16
LISN	VN1-13S	004023	CRANAGE	2024/6/17	2025/6/16

Radiated emission					
Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
EMI Test Receiver	ESCI	101178	RS	2024/6/17	2025/6/16
Spectrum Analyzer	N9020A	MY50510202	Agilent	2024/6/17	2025/6/16
Amplifier	BBV 9743 B	00374	SCHWARZBECK	2024/6/17	2025/6/16
Bilog Antenna	VULB9162	00473	SCHNARZBECK	2023/3/19	2025/3/18
Horn antenna	BBHA 9120 D	02622	SCHNARZBECK	2023/3/19	2025/3/18
Preamplifier	BBV 9718D	00042	SCHNARZBECK	2024/6/17	2025/6/16

Harmonic & Flicker					
Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
Harmonics Flicker Test System	AC200A	512369	LAPLACE	2024/6/17	2025/6/16

Electrostatic Discharge					
Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
Electostastic Discharge Generator	HESD 16	006315	HTEC	2024/6/18	2025/6/17

Continuous radiated disturbances					
Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
Bilog Antenna	3142D	00135452	ETS	2024/04/12	2025/04/11
Amplifier (80-1000MHz)	AP801000_250	MPA1708341	SKET	2024/04/12	2025/04/11
Amplifier (1-3GHz)	AP0103_75	MPA1708342	SKET	2024/04/12	2025/04/11
Amplifier (3-6GHz)	AP0206_50	MPA1708343	SKET	2024/04/12	2025/04/11
RF Switch	/	/	EMC TOYO	2024/04/12	2025/04/11
Power Sensor	/	MY41496069	Agilent	2024/04/12	2025/04/11
Signal Generator	N5181B	MY53050432	Agilent	2024/04/12	2025/04/11

EFT/Dip					
Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
Fast Transient Burst Simulator	HCOM PACT52	221003	HTEC	2024/6/17	2025/6/16
CYCLE SAG SIMULATOR	HV2P16T	221302	HTEC	2024/6/17	2025/6/16

Continuous conducted disturbances					
Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
Signal Generator	CDG-7000-25	10904-1	SCHLODER	2024/6/17	2025/6/16
Power Amplifier	CDG 6050-100	191103	SCHLODER	2024/6/17	2025/6/16
CDN	M2+3	210319	SCHLODER	2024/6/17	2025/6/16

Power-frequency Magnetic field					
Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
Continuous Wave Simulator	HMFG100	212305	HTEC	2024/6/17	2025/6/16

Surge					
Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
Lightning Surge Generator	HOV 7000	222202	HTEC	2024/6/17	2025/6/16
Lightning Surge Generator	HIM 450	222201	HTEC	2024/6/17	2025/6/16
Lightning Surge Generator	SCDN161	222203	HTEC	2024/6/17	2025/6/16

**3.0 Technical Details**

**3.1 Investigations Requested**

Perform Electromagnetic Interference [EMI] & Electromagnetic Susceptibility [EMS] tests for CE Marking

**3.2 Test Standards**

EN IEC 55014-1:2021	Electromagnetic compatibility- Requirements for household appliances, electric tools and similar apparatus. Part 1: Emission
EN IEC 61000-3-2:2019+A1:2021	Electromagnetic compatibility(EMC)- Part 3-2:Limits-Limits for harmonic current emissions(equipment input current $\leq$ 16A per phase)
EN 61000-3-3:2013/A2:2021	Electromagnetic compatibility (EMC)- Part 3-3:Limits-Limitation of voltage changes, Voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current $\leq$ 16A per phase and not subject to conditional connection
EN IEC 55014-2:2021	Electromagnetic compatibility- Requirements for household appliances, electric tools and similar apparatus. Part 2: Immunity-Product family standard

**3.3 Performance Criteria**

**Criterion A** The apparatus shall continue to operate as intended during the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer. The minimum level may be instead of that, either being derived from the product description and documentation, and from what the user may reasonably expect from the apparatus if used as intended.

**Criterion B** The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer. During the test, degradation of performance is allowed, however, no change of actual operating state or stored data is allowed. The minimum level may be instead of that, either being derived from the product description and documentation, and from what the user may reasonably expect from the apparatus if used as intended.

**Criterion C** Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls, or by any operation specified in the instruction for use.

For further performance criteria details, please refer to Table 15 ~ Table 18 in EN IEC 55014-2.

3.4 Test standards and Results Summary Tables

Test Condition	Test Requirement	Test Method	Test Result
<b>EMISSION Results Summary</b>			
Conducted Emission on AC Mains, 150KHz to 30MHz	EN IEC 55014-1	EN IEC 55014-1	Pass
Disturbance Power Test, 30 MHz to 300MHz	EN IEC 55014-1	EN IEC 55014-1	N/A
Radiated Emissions, 30MHz to 1000MHz	EN IEC 55014-1	EN IEC 55014-1	Pass
Harmonic Emissions on AC supply	EN IEC 61000-3-2	EN IEC 61000-3-2	Pass
Voltage fluctuations on AC supply	EN 61000-3-3	EN 61000-3-3	Pass
<b>IMMUNITY Results Summary</b>			
Electrostatic Discharge	EN IEC 55014-2	EN 61000-4-2	Pass
RF field strength susceptibility	EN IEC 55014-2	EN IEC 61000-4-3	Pass
Electrical Fast transients /Burst Immunity	EN IEC 55014-2	EN 61000-4-4	Pass
Surge	EN IEC 55014-2	EN 61000-4-5	Pass
Conducted susceptibility	EN IEC 55014-2	EN IEC 61000-4-6	Pass
Dips/Voltage Interruption Variation	EN IEC 55014-2	EN IEC 61000-4-11	Pass

Note: N/A=Not applicable


3.5 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	MU
1.	Temperature	±0.1°C
2.	Humidity	± 1.0%
3.	Spurious emissions, conducted	± 3.24dB
4.	All emissions, radiated	± 5.03dB

**4.0 Electromagnetic Interference Test results**

**4.1 Power Line Conducted Emission Test**

**4.1.1 Schematics of the test**



**4.1.2 Test Method and test Procedure**

The test was performed in accordance with EN IEC 55014-1

**4.1.3 Test Equipment**

Please refer to the Section 2

**4.1.4 Power line conducted Emission Limit**

Frequency(MHz)	Limits dB( $\mu$ V)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66.0~56.0*	59.0~46.0*
0.50 ~ 5.00	56.0	46.00
5.00 ~ 30.00	60.0	50.00

- Notes:
- \*decreasing linearly with logarithm of frequency.
  - The lower limit shall apply at the transition frequencies

**4.1.5 Photo documentation of the test set-up**

Please refer to the Section 7

**4.1.6 Test specification:**


Environmental conditions: Temperature: 23° C Humidity: 54% Atmospheric pressure: 101kPa

Frequency range: 0.15 MHz – 30 MHz

**4.1.7 Test result** Pass

Remarks: According to the EN IEC 55014-1


**A Conducted Emission on Live Terminal of the power line (150kHz to 30MHz)**



Trace: 1

No.	Freq MHz	Cable Loss dB	LISN Factor dB/m	Aux Factor dB	Receiver Reading dBuV	Emission Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark
1.	0.162	0.00	9.54	10.16	14.72	34.42	58.20	-23.78	Average
2.	0.162	0.00	9.54	10.16	31.70	51.40	65.38	-13.98	QP
3.	0.194	0.01	9.55	10.15	15.87	35.58	56.20	-20.62	Average
4.	0.194	0.01	9.55	10.15	28.79	48.50	63.84	-15.34	QP
5.	0.226	0.01	9.55	10.14	15.57	35.27	54.59	-19.32	Average
6.	0.226	0.01	9.55	10.14	29.50	49.20	62.61	-13.41	QP
7.	0.307	0.01	9.56	10.13	13.67	33.37	51.28	-17.91	Average
8.	0.307	0.01	9.56	10.13	26.60	46.30	60.06	-13.76	QP
9.	0.435	0.01	9.57	10.12	17.46	37.16	47.50	-10.34	Average
10.	0.435	0.01	9.57	10.12	23.41	43.11	57.15	-14.04	QP
11.	0.743	0.02	9.58	10.10	10.80	30.50	46.00	-15.50	Average
12.	0.743	0.02	9.58	10.10	22.80	42.50	56.00	-13.50	QP

**B Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)**



Trace: 3


No.	Freq MHz	Cable Loss dB	LISN Factor dB/m	Aux Factor dB	Receiver Reading dBuV	Emission Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark
1.	0.194	0.01	9.55	10.15	13.84	33.55	56.20	-22.65	Average
2.	0.194	0.01	9.55	10.15	27.10	46.81	63.84	-17.03	QP
3.	0.302	0.01	9.56	10.13	13.16	32.86	51.45	-18.59	Average
4.	0.302	0.01	9.56	10.13	23.10	42.80	60.19	-17.39	QP
5.	0.363	0.01	9.56	10.13	12.65	32.35	49.45	-17.10	Average
6.	0.363	0.01	9.56	10.13	23.60	43.30	58.65	-15.35	QP
7.	0.428	0.01	9.57	10.12	11.10	30.80	47.67	-16.87	Average
8.	0.428	0.01	9.57	10.12	20.10	39.80	57.29	-17.49	QP
9.	0.494	0.01	9.57	10.12	13.10	32.80	46.13	-13.33	Average
10.	0.494	0.01	9.57	10.12	18.20	37.90	56.10	-18.20	QP
11.	0.727	0.02	9.58	10.10	10.23	29.93	46.00	-16.07	Average
12.	0.727	0.02	9.58	10.10	18.20	37.90	56.00	-18.10	QP

4.2 Disturbance Power Test

4.2.1 Test Method:

The test was performed in accordance with EN IEC 55014-1

Block diagram of Test setup



4.2.2 Test Equipment

Please refer to the Section 2

4.2.3 Power line conducted Emission Limit

Frequency(MHz)	Limits dB(pW)	
	Quasi-peak Level	Average Level
30 ~ 300	45~55	35~45

- Notes:
- \*decreasing linearly with logarithm of frequency.
  - The lower limit shall apply at the transition frequencies

4.2.4 Photo documentation of the test set-up

Please refer to the Section 7

4.2.5 Test specification:

Environmental conditions: Temperature: 23° C Humidity: 54% Atmospheric pressure: 101kPa

Frequency range: 30 MHz – 300 MHz

4.2.6 Test result N/A

Remarks: According to the EN IEC 55014-1

**A. Conducted Disturbance Power on AC Line (30MHz to 300MHz)**

EUT Description: --

Operation Mode: --

Tested By: --

Test date: --

Test Result: --

Remark: The test item is not applicable.

**B. Conducted Disturbance Power on DC Line (30MHz to 300MHz)**

EUT Description: --

Operation Mode: --

Tested By: --

Test date: --


Test Result: --

Remark: The test item is not applicable.

4.3 Radiated Emission Test

4.3.1 Test Method: The test was performed in accordance to EN IEC 55014-1

4.3.2 Block diagram of Test setup



4.3.3 Radiated Emission Limit

Frequency Range (MHz)	Distance (m)	Quasi-Peak limits (dB $\mu$ V/m)
30-230	3	40.00
230-1000	3	47.00

Note: The lower limit shall apply at the transition frequencies

4.3.4 Photo documentation of the test set-up

Please refer to the Section 7

4.3.5 Test Equipment:

Please refer to the Section 2


4.3.6 Test specification:

Environmental conditions: Temperature 23° C Humidity: 54% Atmospheric pressure: 101kPa

4.3.7 Test result Pass


Remarks: According to the EN IEC 55014-1

A. Radiated Emission In Horizontal (30MHz----1000MHz)



No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Preamp Gain dB	Receiver Reading dBμV	Emission Level dBμV/m	Limit dBμV/m	Over Limit dB	Remark
1	38.346	0.33	12.07	0.00	15.23	27.63	40.00	-12.37	QP
2	44.431	0.39	12.59	0.00	14.47	27.45	40.00	-12.55	QP
3	96.436	0.68	10.69	0.00	14.67	26.04	40.00	-13.96	QP
4	216.024	1.10	11.95	0.00	15.42	28.47	40.00	-11.53	QP
5	324.456	1.32	14.71	0.00	14.30	30.33	47.00	-16.67	QP
6	411.824	1.45	15.98	0.00	15.21	32.64	47.00	-14.36	QP

**B. Radiated Emission In Vertical (30MHz----1000MHz)**




No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Preamp Gain dB	Receiver Reading dBμV	Emission Level dBμV/m	Limit dBμV/m	Over Limit dB	Remark
1	33.917	0.29	10.84	0.00	21.30	32.43	40.00	-7.57	QP
2	39.299	0.34	12.32	0.00	19.54	32.20	40.00	-7.80	QP
3	55.221	0.47	12.16	0.00	15.29	27.92	40.00	-12.08	QP
4	65.343	0.53	10.43	0.00	16.24	27.20	40.00	-12.80	QP
5	85.598	0.63	9.81	0.00	16.20	26.64	40.00	-13.36	QP
6	96.436	0.68	10.69	0.00	16.70	28.07	40.00	-11.93	QP

4.4 Harmonic Current Emissions

4.4.1 EUT Operating Mode  
Charging

4.4.2 Block Diagram of Test Setup.



This test was performed as per EMC Basic Standard EN IEC 61000-3-2 Class A

4.4.3 Test Equipment

Please refer to Section 2 this report.

4.4.4 Test specification:

Environmental conditions: Temperature: 23° C Humidity: 54% Atmospheric pressure: 101kPa


4.4.5 Results

Port	EUT Operating mode	Result (Passed / Failed)
AC Input	Charging	Passed

4.5 Flicker and Voltage Fluctuation

4.5.1 EUT Operating Mode  
Charging

4.5.2 Block Diagram of Test Setup.



This test was performed as per EMC Basic Standard EN 61000-3-3

4.5.3 Limits of Voltage Fluctuation and Flicks Measurement

Test Item	Limit	Note
P <sub>st</sub>	1.0	Pst means short-term flicker indicator
P <sub>lt</sub>	0.65	Plt means long-term flicker indicator
T <sub>dt</sub> (ms)	200	Tdt means maximum time that dt exceeds 3%.
d <sub>max</sub> (%)	4	Dmax means maximum relative voltage change.
dc (%)	3.3	Dc means relative steady-state voltage change.

4.5.4 Test Equipment

Please refer to Section 2 this report.

4.5.5 Test specification:

Environmental conditions: Temperature: 23° C Humidity: 54% Atmospheric pressure: 101kPa


4.5.6 Results

Port	EUT Operating mode	Result (Passed / Failed)
AC Input	Charging	Pass

**5.0 Immunity Test**

**5.1 Electrostatic Discharge**

**5.1.1 Schematic of the test**



**5.1.2 Test method**

The test was performed in accordance with EN 61000-4-2

**5.1.3 Test severity**

±4kV for direct & in-direct Contact Discharge

±8kV for air Discharge

Performance Criterion Require: **B**

**5.1.4 Test Equipment**

Please refer to Section 2 this report.

**5.1.5 Test specification:**

Environmental conditions: Temperature: 23° C Humidity: 54% Atmospheric pressure: 101kPa

**5.1.6 Operation mode:**

Working

**5.1.7 Discharge location**

- HCP
- VCP
- Enclosure
- Slit
- Metal
- Port

**5.1.8 Test Result**

Pass

5.2 RF field strength susceptibility (80MHz----- 1000MHz)

5.2.1 Test Method:


The test was performed in accordance with EN IEC 61000-4-3

Severity: Level 2 (3V/m)

Modulation: 1 KHz 80% AM

Performance Criterion Require: A

Block diagram of Test setup



5.2.2 Test Equipment

Please refer to Section 2 this report.

5.2.3 Test specification:

Environmental conditions: Temperature: 23° C Humidity: 54% Atmospheric pressure: 101kPa

5.2.4 Operation mode: Working


5.2.5 Test Result:

Please refer to the following table for individual results.

Frequency (MHz)	Radiation to	Polarity	Level (V/m)	Dwell Time(s)	Sweep Rate (%)	Results
80-1000	Front	Horizontal	3	1	1	Pass
80-1000	Rear	Horizontal	3	1	1	Pass
80-1000	Left	Horizontal	3	1	1	Pass
80-1000	Right	Horizontal	3	1	1	Pass
80-1000	Front	Vertical	3	1	1	Pass
80-1000	Rear	Vertical	3	1	1	Pass
80-1000	Left	Vertical	3	1	1	Pass
80-1000	Right	Vertical	3	1	1	Pass

5.3 Electrical Fast Transient/Burst (EFT/B) immunity test

5.3.1 Schematics of the test




5.3.2 Test Method

The test was performed in accordance with EN 61000-4-4

Severity: Level 2 (1kV)

Performance Criterion Require: **B**

Block diagram of Test setup



5.3.3 Test Equipment

Please refer to Section 2 this report.

5.3.4 Test specification:

Environmental conditions: Temperature: 23° C Humidity: 54% Atmospheric pressure: 101kPa

5.3.5 Operation mode: Charging

5.3.6 Test Results


Inject location: AC mains

Inject Line	Voltage kV	Inject Times (s)	Method	Results
L	±1	120	Direct	Pass
N	±1	120	Direct	Pass
L、N	±1	120	Direct	Pass
E	±1	120	Direct	N/A
L、E	±1	120	Direct	N/A
N、E	±1	120	Direct	N/A
L、N、E	±1	120	Direct	N/A

Note: N/A=Not applicable

5.4 Surge test

5.4.1 Schematics of the test




5.4.2 Test Method:

The test was performed in accordance with EN 61000-4-5

Severity: Level 2

Performance Criterion Require: B

Block diagram of Test setup



5.4.3 Test Equipment

Please refer to Section 2 this report.

5.4.4 Test specification:

Environmental conditions: Temperature: 23° C Humidity: 54% Atmospheric pressure: 101kPa

5.4.5 Operation mode: Charging

5.4.6 Test Results

5 pulses for each polarity and test voltage, and repetition rate is 1 per min.


Location	Polarity	0°	90°	180°	270°	Results
L-N	+1 KV	N/A	n.r.r.	N/A	N/A	Pass
	-1 KV	N/A	N/A	N/A	n.r.r.	Pass
L-PE	+2 KV	N/A	N/A	N/A	N/A	N/A
	-2 KV	N/A	N/A	N/A	N/A	N/A
N-PE	+2 KV	N/A	N/A	N/A	N/A	N/A
	-2 KV	N/A	N/A	N/A	N/A	N/A

Remark: 1) n.r.r. = no reaction recognized, N/A = not applicable.

2) Performance Criteria A Observed.

5.5 Conducted immunity test

5.5.1 Schematics of the test




5.5.2 Test Method

The test was performed in accordance with EN IEC 61000-4-6

Severity: Level 2 (3 V rms),

Performance Criterion Require: A

Block diagram of Test setup



5.5.3 Test Equipment

Please refer to Section 2 this report.

5.5.4 Test specification:

Environmental conditions: Temperature: 23° C Humidity: 54% Atmospheric pressure: 101kPa


5.5.5 Operation mode: Charging

5.5.6 Test Results:

Frequency Range (MHz)	Injected Position	Strength	Criterion	Result
0.15 - 80	AC Line	3V (rms) Unmodulated	A	Pass
80-230	AC Line	3V (rms) Unmodulated	A	Pass

5.6 Voltage Dips/Interruptions immunity test

5.6.1 Schematics of the test




5.6.2 Test Method:

The test was performed in accordance with EN IEC 61000-4-11

Performance Criterion Require: C&B

Block diagram of Test setup



5.6.3 Test Equipment

Please refer to Section 2 this report.

5.6.4 Test specification:

Environmental conditions: Temperature: 23° C Humidity: 54% Atmospheric pressure: 101kPa

5.6.5 Operation mode: Charging

5.6.6 Test Result:

Test Level % Ut	Voltage dips & short interruptions % Ut	Duration(in period)	Phase Angle	Criterion	Result
<b>50Hz</b>					
0	100	0.5P	0° - 360°	B	Pass
40	60	10P	0° - 360°	C	Pass
70	30	25P	0° - 360°	C	Pass
<b>60Hz</b>					
0	100	0.5P	0° - 360°	B	Pass
40	60	12P	0° - 360°	C	Pass
70	30	30P	0° - 360°	C	Pass

## 6.0 CE Label


### 6.1 label specification

Text of the mark is black or white in color and is left justified. Labels are printed in indelible ink on permanent adhesive backing and shall be affixed at a conspicuous location on the EUT or silk-screened onto the EUT.




### 6.2 Mark Location: On the product body

**7.0 Photos of testing**  
Radiated Emission Test View



ESD Test View



8.0 Photographs – E.U.T.









--End of the report--